

ORANGE LABEL



100 %
Recycled



70
ISO



80
gsm

Saveco Orange Label office paper is made from 100% recycled fibre in an integrated, energy-efficient and resource-friendly process that is entirely chlorine free. This high-performance multi-purpose paper has excellent eco credentials, including Blue Angel and FSC Recycled® certification. Ideal for all types of corporate communications, it comes in a wide range of sizes and weights. It also offers excellent runnability and processing as per **DIN EN 12281**.



Technical data

Grammage

ISO 536

g/m²

80 ± 3,2

Thickness

ISO 534

µm

102 ± 6,0

ISO brightness

ISO 2470

%

70 ± 2,5

CIE whiteness

ISO 11475

%

65 ± 2,5

Opacity

ISO 2471

%

> 95

Bendtsen roughness

ISO 8791-2

ml/min.

260 ± 160

Certification



www.blauer-engel.de/uz14a



Runnability/ resistance to ageing



Product complies with
DIN EN 12281; resistant to
ageing as per ISO 20494.

Product description

Raw material

Filler

Surface

Sizing

Auxiliary material

Multifunctional office paper for laser and inkjet printers

Mixtures of waste paper, according to the regulations of the Blue Angel (DE-UZ 14a)

kaolin and calcium carbonate

starch treated

neutral sizing with synthetic sizing agents

the auxiliary material used are free from organic chlorine compounds and do not lead to the formation of AOX

Application areas

photocopiers, side printer (LED, laser, magnet, ions), inkjet printer, pre-printing

Assortment

80, 90, 100 and 120 g/gsm

A4, A3, SR A3 and reels,

as well as punched, double and 4 times punched

Further products on request

Manufacturer

Schönfelder Papierfabrik GmbH

Tannenberger Straße 4

09456 Annaberg-Buchholz – Germany

Certifications of the manufacturer



Storage conditions

optimal room temperature min. 10 °C max. 30 °C

Relative humidity min. 30% RH max. 70% RH

Close opened package again when not in use

Processing recommendation

Allow the paper to adapt to the room climate 24 hours before use.

Best runability between 18 °C and 24 °C temperature and between 40% RH and 60% RH relative humidity

Recycling

This product can be 100% recycled after use.